Roll No. .....

## 22224

## M. Tech. 1st Sem. Mechanical Egg. (Machine Design)

## Examination – December, 2013

## **METAL FORMING ANALYSIS**

Paper: M-807-A

Time: Three hours]

[ Maximum Marks: 100

Before answering the questions, candidates should ensure that they have been supplied the correct and complete question paper. No complaint in this regard, will be entertained after examination.

Note: Answer any five questions.

 For the given state of stress, determine the principal stresses and their directions. Also check for the invariance.

$$\tau_{ij} = \begin{bmatrix} 1 & 2 & 1 \\ 2 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$$

**2.** (a) Consider frictionless plane strain compression under conditions of homogeneous deformation. Describe the following quantities: stress and

|    |            | stress, and effective strain.   |
|----|------------|---|
|    | (b)        | Describe three dimensional Mohr's circle of stresses and strains. Also describe the stress tenors and stress invariants.  |
| 3. | (a)        | Develop the equations of the displacement<br>tensors for a condition of a strain at a point. Also<br>explain the strain tensor and rotation tensor. 10                          |
|    | (b)        | What is yielding? Explain yielding criteria for ductile materials.  |
| 4. | Exp<br>FEI | olain in detail the schematic implementation of M for the solution of plastic flow problems. 20   |
| 5. | (a)        | Whether the deformation theory may be used reasonably instead of flow theory for calculating stresses and strains in plastically deformed rotating disc. If yes why? If no why? |
|    | (b)        | What is upper bound theorem? 10   |
| 6. | (a)        | What roll load is required to roll 500mm×2.5mm mild steel strip previously rolled, 30% to 2.4mm thick with 350mm dia steel rolls?   |
|    | (b)        | Is the value of Poisson's ratio different for hot and cold working? Justify your answer. 10   |
| 7. | squ        | aluminium alloy is hot extruded at 400°C through ares dies without lubrication from 125mm dia to am dia. The extrusion speed is 45mm/s. The flow                                |

strain tensor, principal stresses, principal strains, hydrostatic stress, deviatoric stress, effective

450mm. Determine the extrusion load.

stress at 400 °C is  $250N/mm^2$ . The length of the billet is

20

8. Write short notes on the following:

 $5 \times 4 = 20$ 

- (a) The effect of temp. in metal working
- (b) Strain rate in Metal working
- (c) Anisotropy in yielding
- (d) Effect of friction and lubrication on metal working